

## **AMENDMENT**

Please amend the above-identified application as follows:

### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listing, of claims in the application.

1. (Original): A system for providing two qualities of service from a single data stream, comprising:

(a) a storage space for storing at least one of a first quality of service choice and a second quality of service choice for each of a plurality of users;

(b) a processor programmed to direct the data stream for each user according to that user's quality of service choice;

(c) multicasting apparatus for receiving the data stream from the processor and multicasting the data stream to each user for which the first quality of service choice is stored in said storage space; and

(d) a point-to-point device for receiving the data stream from the processor and ensuring that each user for which the second quality of service is stored in said storage space receives the data stream.

2. (Original): A system according to claim 1, further comprising a listener adapted to listen for information sent in the data stream to one of the users of the system.

3. (Original): A system according to claim 1, further comprising a single API for providing instructions to the processor for both qualities of service.

4. (Original): A system according to claim 1, further comprising a thread of execution for each user selecting the multicast quality of service, the thread of execution listening on the user's behalf for a message on the multicast stream then delivering the message to the user.

5. (Currently Amended): A system according to claim [[1]] 2, further comprising a queue for each listener, allowing a user to receive messages for both qualities of service.

6. (Original): A system according to claim 1, wherein said storage space may store separate choices for each user for multiple data streams.

7. (Original): A system according to claim 1, further comprising a filtering device allowing a user to filter out certain messages in the data stream.

8. (Original): A method for allowing a user to select a quality of service for message delivery, comprising:

(a) storing at least one of a first quality of service choice and a second quality of service choice for each user of the system;

(b) processing each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;

(c) multicasting the message to each user selecting the first quality of service; and

(d) sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.

9. (Original): A method according to claim 8, further comprising the step of filtering the messages received by a user by either quality of service

10. (Original): A method according to claim 8, further comprising the step of providing a listener for each user to listen for messages on the user's behalf.

11. (Original): A method according to claim 8, further comprising the step of queuing messages sent to a user by either quality of service to be delivered one by one to the user.

12. (Original): A method according to claim 8, further comprising the step of tagging each message with a sequence number so that a user can tell if a message has been missed.

13. (Original): A method according to claim 8, further comprising the step of tagging each message so that a user can tell the data stream from which the message was received.

14. (Original): A method according to claim 9, further comprising the step of allowing a user to select filtering criteria to be used for the filtering.

15. (Original): A method for providing two qualities of service from a single data stream, comprising:

- (a) storing at least one of a first quality of service choice and a second quality of service choice for each of a plurality of users;

- (b) directing each message received on the data stream for each user according to that user's quality of service choice;

- (c) multicasting the message to each user selecting the first quality of service; and

- (d) sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.

16. (Original): A method according to claim 15, further comprising the step of filtering the messages received by a user by either quality of service.

17. (Original): A method according to claim 15, further comprising the step of providing a listener for each user to listen for messages on the user's behalf.

18. (Original): A method according to claim 15, further comprising the step of queuing messages sent to a user by either quality of service to be delivered one by one to the user.

19. (Original): A method according to claim 15, further comprising the step of tagging each message with a sequence number so that a user can tell if a message has been missed.

20. (Original): A method according to claim 15, further comprising the step of tagging each message so that a user can tell the data stream from which the message was received.

21. (Original): A computer-readable medium, comprising:

(a) means for storing at least one of a first quality of service choice and a second quality of service choice for each user of a system;

(b) means for processing each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;

(c) means for multicasting the message to each user selecting the first quality of service;

and

(d) means for sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.

22. (Original): A computer program product for execution by a server computer for allowing a user to select a quality of service for message delivery, comprising:

(a) computer code for storing at least one of a first quality of service choice and a second quality of service choice for each user of a system;

(b) computer code for processing each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;

(c) computer code for multicasting the message to each user selecting the first quality of service; and

(d) computer code for sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.

23. (Original): A system for allowing a user to select a quality of service for message delivery, comprising:

(a) means for storing at least one of a first quality of service choice and a second quality of service choice for each user of a system;

(b) means for processing each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;

(c) means for multicasting the message to each user selecting the first quality of service; and

(d) means for sending the message directly to each user selecting the second quality of service and ensuring that the user receives the message.

24. (Original): A computer system comprising: a processor;  
object code executed by said processor, said object code configured to:
- (a) store at least one of a first quality of service choice and a second quality of service choice for each user of a system;
  - (b) process each message received on a data stream using a single API and redirecting the message for each user according to that user's quality of service choice;
  - (c) multicast the message to each user selecting the first quality of service; and
  - (d) send the message directly to each user selecting the second quality of service and ensuring that the user receives the message.
25. (New) The system of claim 1, wherein the point-to-point device ensures that each user receives the data stream by receiving a response from that user, which delivers an acknowledgement of the receipt of data.
26. (New) The method of claim 8, wherein the step of ensuring that the user receives the message includes receiving a response which delivers an acknowledgement of the receipt of data from that user.
27. (New) The method of claim 15, wherein the step of ensuring that the user receives the message includes receiving a response which delivers an acknowledgement of the receipt of data from that user.
28. (New) The computer-readable medium of claim 21, wherein the means for ensuring that the user receives the message includes receiving a response which delivers an acknowledgement of the receipt of data from that user.
29. (New) The computer program product of claim 22, further comprising:  
computer code for receiving a response from each user selecting the second quality of service, which delivers an acknowledgement of the receipt of data.

30. (New) The system of claim 23, further comprising:  
ensuring that each user selecting the second quality of service receives the message by  
receiving a response from that user, which delivers an acknowledgement of the receipt of data.